

Further surveyed by D.S. Maurer Deputy, S.C.C. March 23<sup>rd</sup> 1893. S.T.L. Miles and M. New chain carriers sworn.

No. 9.	Sand Stone	21 in	at corner,		
" "	" "	16 "	" "	(N. "	30 lbs.
" 10.	" "	mt. 18 in	" "		
" "	Sugar.	13 "	" "	S 32 E.	60 "
" 11.	Sand Stone	mt. 22 "	" "		
" "	Ash.	13 "	" "	N 86 E.	93 "

Further surveyed by Thomas B. Robertson Surveyor of Clay county Indiana Nov. 25<sup>th</sup> 1893 by request of "Will" Vader and consent of Phillip Vader the only persons effected in the survey.

Cor. 12 a Sand Stone marked T. Is 2.52 chains west of center of the S.W. quarter.

Cor. 13 a Sand Stone marked V. - Is N. 14° E. 8.22<sup>2</sup>/<sub>3</sub> chains distant from corner No. 12.

Corner No. 14 a Sand Stone marked V - Is S 64° E. 5.71 chains distant from corner No. 13.

Corner No. 15 a Sand Stone marked + Is S 3° 15' E. 5.66 chains distant from Cor. No. 14. and on the 1/4 mile line, and 5.08 chains East from the center of the S.W. qr.

Thomas B. Robertson Surveyor of Clay Co. Indiana