Further Surveyed by Thomas B. Robertson Surveyor of Clay county Indiana 1894, by request of Garnet Corbin and consent of parties interested chainmen and flagman sworn as the law requires and Corners 9, 10, 11, 12 set and 5 and 6 reset

Corner 9 A Sand Stone 18 in. Mr. 1/16 - set 2 feet South of proper place, on account of culvert.

Witness a Sand Stone Mr. W N 37½° W. 42½ Links

Cor. 10 A Sand Stone Mr. K - Witness a Sand Stone Mr. W. S 3¼° E. 34¾ Lks

Cor. 11. A Nigger head 14×15 in. 20 Rods South of 6.

Witness a Niggerhead S. 10½° W. 26 Links

Cor 12 A. Sand Stone Mr. T - Wit. a Sand Stone Mr. W. S 88½° W. 25 Links

Cor. 6 (Reset) Niggerhead Mr ¼ Wit a Nigh. 10½ in. N 25½ E. 47¾ Lks.

Cor. 5 " A Sand Stone Mr. 1/16 - Wit. a Sand Stone Mr. W. N. 8½ E. 53½ Lks

" 13 Grate Bar 26 in Long set at Corner

Niggerhead 10 East 25 Lks

" 14 Pump Joints 18 in long

15 Grate Bar 26 in

Sand Stone 8 in West 25 Lks