Corner No. 6. Sand Stone, marked +
" " " " " N 84 E. 27 lks.
Corner No 7. Sand Stone marked +.
" " " Nigger Head due North 66 Links.
" " " Jack Oak 9 N 24 E. 58 " .

J. C. Burns. S. C. C.

Further Surveyed by Thomas B Robertson Surveyor of Clay Co. May 27th 1893 corners set from 8-9 by request of J. M. Gilbert and Geo. W. Vancleve they being the only parties interested. J. M. Gilbert and G. W. Vancleve chainmen.

Cor. No 8 A "Nigger head" 8 x 11 inches set 40 Rods south of the North half mile corner.

Cor. No 9 A Sand Stone marked 40, set 40 Rods south from the North west corner of the East half of the North west quarter
"Niggerhead" 7 x 9 North in line 22 7/8 Links
Wild Cherry 10 inches. N. S. 4° 30' W. 37 3/8 Lks - No Var.

Cor - 10 "Niggerhead" 15 inches -
Wild Cherry 12 S. 75 1/4 W. 52 1/2 Links
Black Oak 26 S. 26 E. 67 "

Cor 11 A Sand stone marked 1/16 (Broken dishes under stone)

Cor. 12 A "Niggerhead" 15 inches - Black Oak 12 inches S. 28° W. 57 Lks
"Niggerhead 8 x 12 S. 42° 15' E. 43 Lks.

Cors. 10, 11 & 12 were set by John J. Hayden April 23rd 1891, but not recorded
Recorded this 27th of May 1893 - J. M. Gilbert & G. W. Vancleve chainmen and
T. B. Robertson flagman, for Cor. 10, 11 and 12

Thomas B Robertson Surveyor C. C.

Cors. 13, 14, 15, 16 & 17 ~~set~~ 1889 Set by request of Jos. Smith and James M. Gilbert and consent of interested parties.

Cor. 13 A Flint stone 10 inches long 10 Rods West from 1/2 mile cor Wit. Flint S 49 W. 30 lk.
" 14 " Sand Stone 11 inches. Wit - Stone N 87° E 21 ft. 3 in 16 Rods South from 13
Cor. 15 " Flint Stone 13 in. 16 Rods South from 1/2 mile corner.
" 16 " Sand Stone marked 10 - 10.0925 South from center of section
" 17 " Sand Stone Mr. "S.P." at center of E 1/2 of the S.W. qr.
" 18 " Sand Stone Mr. 10 at center of N.E. qr. of S.W. qr.

Thomas B Robertson S. C. C.

Cor 22	Round	Nig head set		S	20	Rods	west of	Cor	20	A o	Witness
" 23	"	"	"		30	Rods	"	"	"	22	" "
24	"	"	"		30	"				25	
25	"	"	"		20	"				21	