

- Corner N. 8 Niggerhead 16 ins long at Center of N. E. q. r. sec
 " " " " " a White Oak 29 N 29 E 16 links
 " " " " " a do 36 S 80 E 9 "
 " "9 Niggerhead 11 ins long at middle of line N. of Center of sec to $\frac{1}{2}$ m. cor.
 " " " " " a White Oak 36 S $6\frac{3}{4}$ E. 63 links
 " " " " " a do. 28 N 6 E. $6\frac{1}{2}$ do
 " "10 Niggerhead 29 ins long at middle of W. line of N. W. q. r.
 " " " " " an Ash 18 N $1\frac{1}{2}$ W. 159 links
 " " " " " a Locust 20 S $23\frac{1}{2}$ W. $174\frac{1}{2}$ links
 " "11 Niggerhead 21 ins long at middle of N. line of N. E. q. r.
 " " " " " a White Oak 36 N 86 W. 130 links
 " " " " " a Niggerhead 12 ins long S 50 do.
 " "12 Niggerhead 18 ins long at $\frac{1}{2}$ mile cor. on N. line of sec.
 " " " " " a Bur Oak 29 S 9 W 80 links
 " " " " " a do 12 N $4\frac{1}{2}$ W $7\frac{1}{2}$ do
 " "13 Niggerhead 15 ins long at middle of N. line of N. W. q. r.
 " " " " " a Niggerhead 13 ins long S 50 links
 " "14 Sand Stone ^{18 ins long} 83.4 N. of S. W. cor of sec & 74.6 S of W $\frac{1}{2}$ mile cor
 " " " " " an Austrian Pine 4 S $35\frac{1}{2}$ E. 89 links
 " "15 Niggerhead 14 ins long N. of line sec line 83.4 Rods
 " "16 Niggerhead 12 " " E. of cor N. 13.2 Rods
 " "17 Niggerhead 12 ins long at middle of S. line of N. W. q. r. & N. line of sec
 " " " " " a White Oak 29 S 10 E 125 links
 " " " " " a White O. stump 77 W. $22\frac{1}{2}$ do
 " "18 Niggerhead 13 ins long at center of N. W. q. r. of sec.
 " " " " " a White Oak 34 N 52 W 40 links
 " " " " " a do 24 S 58 E 77 do
 " "19 Sand Stone 30 Rods E of S. W. cor of S. E. q. r. of S. E. q. r.
 " " " " " a Jack Oak 14 N 36 links
 " " " " " a do. — N 48 W. $60\frac{1}{2}$ lks
 " "20 Flint Stone 9 ins long 30 Rods E of S. W. cor of S. E. q. r. of S. E. q. r.
 " " " " " a Black Oak 8 S $\frac{1}{2}$ link
 " " " " " a White Oak 20 S $2\frac{1}{2}$ E 72 lks
 " "21 Sand Stone 18 ins long S. E. cor. of sec. cor sec 5 @ 17 @ 2. Set
 " " " " " from Original Bearing—White Oak.
 " " " " " W. a White Oak 24 N 8 E. 135 links
 " " " " " Corner sticks S. C. C.

Further Surveyed by Geo. A. Sheehan, Surveyor Clay County, Apr 25, 1912
 at request of Henry Whalen et al. James Elder Chairman, duly sworn
 Corner # 22 Sand stone marked X 12" x 6" x 5" 467.5 ft. N. of ()
 Witness Flint stone on top sand stone N 15 feet
 Blue Flint stone N 90° W 15 "