

Second Meridian.

Further surveyed June-1-1916, at the request of John Triplett. Interested parties consenting.
Surveyed by Geo. W. Sheehan - Surveyor, Clay County.

Cor. #3 Reset. Flint Stone - + - Angle Iron $30^{\circ}0'E$ - 15 Feet

Cor. #4 Sand Stone - + - $956'-0"$ South of Cor. #3

Sand stone $N72\frac{1}{2}^{\circ}W$ 15 Feet.

Cor. #5 Concrete Post $1'-5" \times 3" \times 3"$ North of ~~to~~ National Road 40 feet

Concrete Post $N20^{\circ}0'W$ 15 Feet

Cor. #6 Sand Stone - + - $1882.60'$ South of Cor. #7 and
 $624'-0"$ South West of Cor. #5 - $40'$ North of ~~to~~ National Road
Angle $N75^{\circ}E$ - 31 Feet

Cor. #7 Pump Jack $1'-9"$ long - $471'-0"$ West of Center of Section.
Small Conduit $1'-6"$ long $52^{\circ}0'E$ 15 Feet.

The Red Outline is Boundary of work done.

1145' To N.E. Cor.
Sec. 28, T. 13 N. R. 6 W.

A part of the $E\frac{1}{2}$ of the N.E. $\frac{1}{4}$
Section 28, Township 13, North
Range 6 West.

SURVEY: Requested by Joseph Riddell
and wife. John Dugan and wife the
other interested party duly notified,
and chain man sworn in. Survey made
Sept. 14, 1953, and corners located
as shown on above plat. 20 pwt. nails
set at corners on East line, and
wooden stakes at all other corners.
Survey made by Oscar J. Jenkins
County Surveyor of Clay County.

