

Second Meridian.

Corner 11. A sand stone 18 in. marked $\frac{1}{16}$ S
 Witnessed by a sand stone (min.) South $35\frac{1}{2}$ Sks.
 " 12. A sand stone marked $\frac{1}{16}$
 Witnessed by a sand stone marked East $29\frac{1}{2}$ S.
 The distance from 5 to 2 is 78.90 chains - from 4 to 5 -
 40 chains. - from 7 to 4 is ~~40.80~~ 40.80 chains. - from 1 to
 2 is 81.675 chains, and the west side of the section is
 79.86 chains.

We the undersigned land owners hereby agree
 that the county Surveyor shall survey and
 establish lines and corners of our lands in
 Section 3 T. 9 R. 6 and that we will all be bound
 and abide by the result thereof. May 6th 1893.

Robert Guthrie Ade Nanglebaugh, John Gotter
 Jacob Storm, George Garlits Thomas Foxworthy
 G. P. Gray. Recorded this 26th day of May, A.D. 1893
 Thomas B. Robertson, Surveyor of Clay Co.

FORM I C-614

State Form 4288

10M 8-81

INDIANA DEPARTMENT OF HIGHWAYS CONSTRUCTION RECORD

PAGE No. _____

PROJ. NO. _____

SECTION _____

STR. NO. _____

CONTRACT No. _____

DETAIL SKETCH

ITEM No. _____